

EDGE TRI-CURVE LINEAR

4', 8'
 Single Channel Distribution
 15% Indirect, 85% Direct
 UL 924, UL 1598, UL 2108
 100% Recycled Aluminum
 Recyclable Steel and Acrylic
 Advanced Dimming 0-10V, Down to 1%
 L90>71,000
 5-Year Warranty



UL Certified for Elevated Ambient
 Operating Temperatures
 70°C Remote
 55°C Integral

Remote Distributed Low Voltage
 Integral Class 2 Driver 120-277V
 Integral with Onboard Emergency
 Power over Ethernet (PoE)

Available Colors



Remote

Size	4 ft	122 cm	8 ft	240 cm
Length	47.1 in	119.7 cm	93.2 in	236.7 cm
Width	5.5 in	14 cm	5.5 in	14 cm
Height	2.2 in	5.5 cm	2.2 in	5.5 cm
Weight	7 lbs	3.2 kg	13.0 lbs	5.9 kg

Integral

Size	4 ft	122 cm	8 ft	240 cm
Length	47.1 in	119.7 cm	93.2 in	236.7 cm
Width	5.5 in	14 cm	5.5 in	14 cm
Height	3.5 in	8.9 cm	3.5 in	8.9 cm
Weight	7 lbs	3.2 kg	13.0 lbs	5.9 kg

LUMEN PACKAGES Delivered Lumens tested at 4000K 80 CRI

Size	SKU	Watts	Integral		Remote	
			157.13 Lm/W 80 CRI	130 Lm/W 90 CRI	155.5 Lm/W 80 CRI	129 Lm/W 90 CRI
4'	L1	20	3143	2608	3110	2581
	L2	30	4714	3913	4665	3872
	L3	40	6285	5217	6220	5163
8'	L1	40	6285	5217	6220	5163
	L2	60	9428	7825	9330	7744
	L3	80	12570	10433	12440	10325

ORDERING INFORMATION

FIXTURE	POWER	SIZE	MOUNT	LUMENS	COLOR	CRI
ETCL-Edge Tri-Curve Linear	I-Integral	4-4 Foot	P-Pendant	L1-	30-3000K	80-80+ CRI
	IEM-Emergency	8-8 Foot	S-Surface	L2-	35-3500K	90-90+ CRI
	R-Remote		U-Unistrut	L3-	40-4000K	
	POE-PoE				50-5000K 65-6500K	
INTEGRAL WHIP	FEED*	SENSOR**				
0-None	TFC-Top Feed Center	ES-Keilton LV - Remote/Integral				
3-No Dim	TFE-Top Feed End	SE-Smartengine PoE - Remote				
5-Dim	SF-Side Feed	LU-Lutron - Integral				
3E-No Dim EM On	*For integral and integral emergency only	EN-Enlighted - Integral				
4E-No Dim EM On/Off		LM-Lantana Microwave - Integral				
5E-Dim EM On		MC-McWong/Casambi - Integral				
6E-Dim EM On/Off						

**Includes sensor, sensor endcap, and installation.
 Sensors are not compatible with emergency battery backup.