

EDGE TRI-FLAT LINEAR

4', 8'
 Single Channel Distribution
 20% Indirect, 80% Direct
 UL 924, UL 1598, UL 2108
 100% Recycled Aluminum
 Recyclable Steel and Acrylic
 Advanced Dimming 0-10V, Down to 1%
 L90>71,000
 5-Year Warranty



UL Certified for Elevated Ambient
 Operating Temperatures
 70°C Remote
 55°C Integral

Remote Distributed Low Voltage
 Integral Class 2 Driver 120-277V
 Integral with Onboard Emergency
 Power over Ethernet (PoE)



Remote

Size	4 ft	122 cm	8 ft	240 cm
Length	47.1 in	119.7 cm	93.2 in	236.7 cm
Width	5.5 in	14 cm	5.5 in	14 cm
Height	1.8 in	4.6 cm	1.8 in	4.6 cm
Weight	7 lbs	3.2 kg	13.0 lbs	5.9 kg

Integral

Size	4 ft	122 cm	8 ft	240 cm
Length	47.1 in	119.7 cm	93.2 in	236.7 cm
Width	5.5 in	14 cm	5.5 in	14 cm
Height	3.2 in	8.1 cm	3.2 in	8.1 cm
Weight	7 lbs	3.2 kg	13.0 lbs	5.9 kg

LUMEN PACKAGES Delivered Lumens tested at 4000K 80 CRI

Size	SKU	Watts	Integral		Remote	
			157 Lm/W 80 CRI	130 Lm/W 90 CRI	154 Lm/W 80 CRI	128 Lm/W 90 CRI
4'	L1	20	3134	2601	3088	2563
	L2	30	4700	3902	4632	3845
	L3	40	6267	5202	6176	5126
8'	L1	40	6267	5202	6176	5126
	L2	60	9401	7804	9264	7689
	L3	80	12534	10405	12352	10252

ORDERING INFORMATION

FIXTURE	POWER	SIZE	MOUNT	LUMENS	COLOR	CRI
ETFL-Edge Tri-Flat Linear	I-Integral	4-4 Foot	P-Pendant	L1-	30-3000K	80-80+ CRI
	IEM-Emergency	8-8 Foot	S-Surface	L2-	35-3500K	90-90+ CRI
	R-Remote		U-Unistrut	L3-	40-4000K	
	POE-PoE				50-5000K 65-6500K	

INTEGRAL WHIP	INTEGRAL FEED*	SENSOR**
0-None	TFC-Top Feed Center	ES-Keilton LV - Remote/Integral
3-No Dim	TFE-Top Feed End	SE-Smartengine PoE - Remote
5-Dim	SF-Side Feed	LU-Lutron - Integral
3E-No Dim EM On	*For integral and integral emergency only	EN-Enlighted - Integral
4E-No Dim EM On/Off		LM-Lantana Microwave - Integral
5E-Dim EM On		MC-McWong/Casambi - Integral
6E-Dim EM On/Off		

**Includes sensor, sensor endcap, and installation. Sensors are not compatible with emergency battery backup.