

ILLUCENT LINEAR

4', 6', 8'

Sustainably Constructed
100% Recycled Aluminum

Recyclable Acrylic
Single Channel Distribution
25% Indirect/75% Direct
UL 924, UL 1598, UL 2108

Advanced Dimming 0-10V, Down to 1%
DALI Tunable White Option
Circadian Options
L90>71,000
10-Year Warranty

UL Certified for Elevated Ambient
Operating Temperatures
70°C Remote
55°C Integral
35°C Emergency Battery

Remote Distributed Low Voltage
Integral Class 2 Driver 120-277V
Integral with Onboard Emergency
Power over Ethernet (PoE)

Available Colors



Remote

Size	4 ft	122 cm	6 ft	180 cm	8 ft	240 cm
Top L	47.0 in	119.4 cm	70.2 in	178.3 cm	93.0 in	234.2 cm
Bottom L	48.2 in	122.4 cm	71.5 in	181.6 cm	94.2 in	239.3 cm
Width	5.5 in	14 cm	5.5 in	14 cm	5.5 in	14 cm
Height	2.6 in	6.6 cm	2.6 in	6.6 cm	2.6 in	10.2 cm
Weight	4.0 lbs	1.8 kg	6.0 lbs	2.7 kg	8.0 lbs	5.4 kg



Integral

Size	4 ft	122 cm	6 ft	180 cm	8 ft	240 cm
Top L	46.2 in	117.3 cm	69.5 in	176.5 cm	92.2 in	234.2 cm
Bottom L	48.2 in	122.4 cm	71.5 in	181.6 cm	94.2 in	239.3 cm
Width	5.5 in	14 cm	5.5 in	14 cm	5.5 in	14 cm
Height	4.0 in	10.2 cm	4.0 in	10.2 cm	4.0 in	10.2 cm
Weight	6.0 lbs	2.7 kg	10.0 lbs	4.5 kg	12.0 lbs	5.4 kg



LUMEN PACKAGES (Delivered lumens tested at 4000K 80 CRI Remote/Integral, 5000k 97 CRI Circadian/Tunable)

Size	SKU	Total Watts	Integral		Remote/PoE		Circadian	Tunable
			162 Lm/W 80 CRI	135 Lm/W 90 CRI	165 Lm/W 80 CRI	137 Lm/W 90 CRI	119 Lm/W 97 CRI	91 Lm/W 97 CRI
4' 122 cm	L1	20	3241	2690	3294	2734	2372	1826
	L2	30	4861	4035	4941	4101	3558	2739
	L3	40	6482	5380	6588	5468	4744	3652
6' 180 cm	L1	30	4861	4035	4941	4101	3558	2739
	L2	45	7292	6052	7412	6152	5337	4109
	L3	60	9722	8070	9882	8202	7116	5478
8' 240 cm	L1	40	6482	5380	6588	5468	4744	3652
	L2	60	9722	8070	9882	8202	7116	5478
	L3	80	12963	10759	13176	10936	9488	7304

ORDERING INFORMATION

FIXTURE	POWER	SIZE	MOUNT	LUMENS	COLOR	CRI	INTEGRAL WHIP
ILIN-Illucent Linear	I-Integral	4-4 Foot	P-Pendant	L1-	30-3000K	80-80+ CRI	3-No Dim
	IEM-Emergency	6-6 Foot	S-Surface	L2-	35-3500K	90-90+ CRI	5-Dim
	R-Remote	8-8 Foot	U-Unistrut	L3-	40-4000K	97-Circadian	3E-No Dim EM On
	POE-PoE				50-5000K		4E-No Dim EM On/Off
				65-6500K		5E-Dim EM On	
				DC-Dynamic Circadian		6E-Dim EM On/Off	
				TW-Tunable White (integral)			
WHIP COLOR*	FEED*	FINISH		ENDCAP	SENSOR**		
W-White	TFC-Top Feed Center	CW-Clear Anodized Aluminum		WP-White Plastic	ES-Keilton LV - Remote/Integral		
B-Black	TFE-Top Feed End	BB-Black Anodized Aluminum		BP-Black Plastic	SE-Smartengine PoE - Remote		
S-Silver Braided	SF-Side Feed	CC-Custom Color		CM-Metal Clear Anodized	LU-Lutron - Integral		
		(certain restrictions apply)			EN-Enlighted - Integral		
					LM-Lantana Microwave - Integral		
					MC-McWong/Casambi - Integral		

*Skip for POE

** Not compatible w/emergency

Specifications subject to change without notice.
Revision Date: 06/01/2024

LANTANA LED

WWW.LANTANALED.COM

ILLUCENT LINEAR CONTINUOUS RUN

Continuous Run up to 100'
 Sustainably Constructed
 100% Recycled Aluminum
 Recyclable Acrylic
 Single Channel Distribution
 25% Indirect/75% Direct
 UL 924, UL 1598
 Advanced Dimming 0-10V, Down to 1%
 DALI Tunable White
 Circadian Options
 L90>71,000
 10-Year Warranty

UL Certified for Elevated Ambient
 Operating Temperatures
 55°C Integral
 35°C Emergency Battery



	End		Mid		End		Mid	
Size	4 ft	122 cm	4 ft	122 cm	8 ft	240 cm	8 ft	240 cm
Top L	46.3 in	117.5 cm	46.3 in	117.5 cm	92.2 in	234.2 cm	92.3 in	234.4 cm
Bottom L	47.3 in	117.5 cm	46.3 in	117.5 cm	94.2 in	239.3 cm	93.3 in	234.4 cm
Width	5.5 in	14 cm	5.5 in	14 cm	5.5 in	14 cm	5.5 in	14 cm
Height	4.0 in	10.2 cm	4.0 in	10.2 cm	4.0 in	10.2 cm	4.0 in	10.2 cm
Weight	6.0 lbs	2.7 kg	6 lbs	2.7 kg	12.0 lbs	5.4 kg	12 lbs	5.4 kg

Available Colors



LUMEN PACKAGES (Delivered lumens tested at 4000K 80 CRI Integral, 5000k 97 CRI Circadian/Tunable)

Size	SKU	Integral		Circadian	Tunable	Total Watts
		162 Lm/W 80 CRI	135 Lm/W 90 CRI	119 Lm/W 97 CRI	91 Lm/W 90 CRI	
4'	L1	3241	2690	2372	1826	20
	L2	4861	4035	3558	2739	30
	L3	6482	5380	4744	3652	40
6'	L1	4861	4035	3558	2739	30
	L2	7292	6052	5337	4109	45
	L3	9722	8070	7116	5478	60
8'	L1	6482	5380	4744	3652	40
	L2	9722	8070	7116	5478	60
	L3	12963	10759	9488	7304	80

ORDERING INFORMATION

FIXTURE	TOTAL LENGTH	MOUNT	LUMENS	COLOR	CRI	INTEGRAL WHIP
ILCR-Illicent Linear Continuous Run	###In Feet	P-Pendant	L1-	30-3000K	80-80+ CRI	3-No Dim
			L2-	35-3500K		5-Dim
		U-Unistrut	L3-	40-4000K	97-Circadian	3E-No Dim EM On
				50-5000K		4E-No Dim EM On/Off
			65-6500K		5E-Dim EM On	
			DC-Dynamic Circadian		6E-Dim EM On/Off	
			TW-Tunable White (integral)			

WHIP COLOR	FEED	FINISH	ENDCAP	SEGMENTS
W-White	TFC-Top Feed Center	CW-Clear Anodized Aluminum	WP-White Plastic	CR2-Integral 2'
B-Black	TFE-Top Feed End	BB-Black Anodized Aluminum	BP-Black Plastic	CR4-Integral 4'
S-Silver Braided	SF-Side Feed	CC-Custom Color (certain restrictions apply)	CM-Metal Clear Anodized	CR6-Integral 6'
				CR8-Integral 8'
				CR4E-Integral Emergency 4'
				CR6E-Integral Emergency 6'
				CR8E-Integral Emergency 8'

TOTAL LENGTH	SEG 1 (WHIP)	SEG	SEG	SEG	SEG	SEG	SEG	SEG	SEG	SEG	SEG	SEG	SEG	SEG (END)

ILLUCENT LINEAR QUICK SHIP

Ships Within 10 Business Days
 Sustainably Constructed
 100% Recycled Aluminum
 Recyclable Acrylic
 Single Channel Distribution
 25% Indirect/75% Direct
 UL 924, UL 1598
 Advanced Dimming 0-10V, Down to 1%
 L90>71,000
 10-Year Warranty

Available to ship within ten business days. Maximum order is 100.



UL Certified for Elevated Ambient Operating Temperatures
 55°C Integral

Integral Class 2 Driver 120-277V

Available Colors

Declare. TAA



Integral Quick Ship

Size	4 ft	122 cm	8 ft	240 cm
Top L	46.2 in	117.3 cm	92.2 in	234.2 cm
Bottom L	48.2 in	122.4 cm	94.2 in	239.3 cm
Width	5.5 in	14 cm	5.5 in	14 cm
Height	4.0 in	10.2 cm	4.0 in	10.2 cm
Weight	6.0 lbs	2.7 kg	12.0 lbs	5.4 kg

LUMEN PACKAGES Delivered Lumens tested at 4000K 80 CRI

Size	SKU	162 Lm/W 80 CRI	135 Lm/W 90 CRI	Total Watts
4'	L1	3241	2690	20
	L2	4861	4035	30
	L3	6482	5380	40
8'	L1	6482	5380	40
	L2	9722	8070	60
	L3	12963	10759	80

ORDERING INFORMATION

FIXTURE	POWER	SIZE	MOUNT	LUMENS	COLOR	CRI	INTEGRAL WHIP
ILQS-Illucent Linear Quick Ship	I-Integral	4-4 Foot	P-Pendant	L1-	30-3000K	80-80+ CRI	3-No Dim
		8-8 Foot	U-Unistrut	L2-	35-3500K	90-90+ CRI	5-Dim
				L3-	40-4000K		
					50-5000K		
					65-6500K		

WHIP COLOR	FEED	FINISH	ENDCAP
W-White	TFC-Top Feed Center	CW-Clear Anodized Aluminum	WP-White Plastic
B-Black	TFE-Top Feed End		
S-Silver Braided	SF-Side Feed		