

# ILLUCENT LINEAR CONTINUOUS RUN

Continuous Run up to 100'  
 Sustainably Constructed  
 100% Recycled Aluminum  
 Recyclable Acrylic  
 Single Channel Distribution  
 25% Indirect/75% Direct  
 UL 924, UL 1598  
 Advanced Dimming 0-10V, Down to 1%  
 DALI Tunable White  
 Circadian Options  
 L90>71,000  
 10-Year Warranty

---

UL Certified for Elevated Ambient  
 Operating Temperatures  
 55°C Integral  
 35°C Emergency Battery



	End		Mid		End		Mid	
Size	4 ft	122 cm	4 ft	122 cm	8 ft	240 cm	8 ft	240 cm
Top L	46.3 in	117.5 cm	46.3 in	117.5 cm	92.2 in	234.2 cm	92.3 in	234.4 cm
Bottom L	47.3 in	117.5 cm	46.3 in	117.5 cm	94.2 in	239.3 cm	93.3 in	234.4 cm
Width	5.5 in	14 cm	5.5 in	14 cm	5.5 in	14 cm	5.5 in	14 cm
Height	4.0 in	10.2 cm	4.0 in	10.2 cm	4.0 in	10.2 cm	4.0 in	10.2 cm
Weight	6.0 lbs	2.7 kg	6 lbs	2.7 kg	12.0 lbs	5.4 kg	12 lbs	5.4 kg

Available Colors



## LUMEN PACKAGES (Delivered lumens tested at 4000K 80 CRI Integral, 5000k 97 CRI Circadian/Tunable)

Size	SKU	Integral		Circadian	Tunable	Total Watts
		162 Lm/W 80 CRI	135 Lm/W 90 CRI	119 Lm/W 97 CRI	91 Lm/W 90 CRI	
4'	L1	3241	2690	2372	1826	20
	L2	4861	4035	3558	2739	30
	L3	6482	5380	4744	3652	40
6'	L1	4861	4035	3558	2739	30
	L2	7292	6052	5337	4109	45
	L3	9722	8070	7116	5478	60
8'	L1	6482	5380	4744	3652	40
	L2	9722	8070	7116	5478	60
	L3	12963	10759	9488	7304	80

## ORDERING INFORMATION

FIXTURE	TOTAL LENGTH	MOUNT	LUMENS	COLOR	CRI	INTEGRAL WHIP
ILCR-Illucent Linear Continuous Run	###In Feet	P-Pendant	L1-	30-3000K	80-80+ CRI	3-No Dim
		U-Unistrut	L2-	35-3500K	90-90+ CRI	5-Dim
			L3-	40-4000K	97-Circadian	3E-No Dim EM On
			50-5000K	65-6500K	DC-Dynamic Circadian	4E-No Dim EM On/Off
			5E-Dim EM On	6E-Dim EM On/Off		
			DC-Dynamic Circadian	TW-Tunable White (integral)		

WHIP COLOR	FEED	FINISH	ENDCAP	SEGMENTS
W-White	TFC-Top Feed Center	CW-Clear Anodized Aluminum	WP-White Plastic	CR2-Integral 2'
B-Black	TFE-Top Feed End	BB-Black Anodized Aluminum	BP-Black Plastic	CR4-Integral 4'
S-Silver Braided	SF-Side Feed	CC-Custom Color (certain restrictions apply)	CM-Metal Clear Anodized	CR6-Integral 6'
				CR8-Integral 8'
				CR4E-Integral Emergency 4'
				CR6E-Integral Emergency 6'
				CR8E-Integral Emergency 8'

TOTAL LENGTH	SEG 1 (WHIP)	SEG	SEG	SEG	SEG	SEG	SEG	SEG	SEG	SEG	SEG	SEG	SEG	SEG (END)