

REMOTE DRIVER UNIT

Max Rating 1720 W Class 2 Electrical Device
 UL 924, UL 2108, NEMA Rating 1
 Sustainably Constructed
 100% Recycled Aluminum
 Controls Agnostic
 Localized On/Off Switch
 Pre-configured/Pre-wired Zones

Ambient Operating Temperatures: 0°C to 50°C
 Humidity: 5% to 95% RH Non-condensing

277 VAC/1.8 A, 50-60 Hz
 120 VAC/4.2 A, 50-60 Hz

<150' - 18/2 GA Wiring
 >150' - 16/2 GA Wiring



RDUX with Single Controls Side Car

Dual Controls Side Car

	RDUX	RDU14	RDU12	RDU6
Weight	42 lbs / 19 kg	30 lbs / 14 kg	25 lbs / 11 kg	14 lbs / 6 kg
W x H x D	28.5 x 27 x 4.5 in 72 x 69 x 11 cm	21.5 x 27 x 4.5 in 55 x 69 x 11 cm	19 x 27 x 4.5 in 48 x 69 x 11 cm	12 x 27 x 4.5 in 30 x 69 x 11 cm
Drivers	Up to 20	Up to 14	Up to 12	Up to 6
		Single Controls Sidecar	Dual Controls Sidecar	
SKU		C	C2	
Dimensions w/Localized Switch Box		17.94 x 12.78 x 5.81 in 46 x 32 x 15 cm +13.50 lbs / 6 kg	26.6 x 12.78 x 5.81 in 68 x 32 x 15 cm +25.25 lbs / 11 kg	
Controllers		1 Dimming 2 Emergency	2 Dimming 4 Emergency	
Zones		1-3 Dimming 2 Emergency	2-6 Dimming 4 Emergency	

ORDERING INFORMATION

REMOTE DRIVER UNIT

RDUX-20 drivers
 RDU14-14 drivers
 RDU12-12 drivers
 RDU6-6 drivers

OPTIONAL CONTROLS SIDECAR*

C- Single Controls Sidecar
 C2-Dual Controls Sidecar

*CONTROLS NOT INCLUDED

ZONE CONFIGURATION

Examples		ZONE 1				ZONE 2				ZONE 3			
		NORMAL		EMERGENCY		NORMAL		EMERGENCY		NORMAL		EMERGENCY	
Zones	Product	Drivers	Fixture Size	Drivers	Fixture Size	Drivers	Fixture Size	Drivers	Fixture Size	Drivers	Fixture Size	Drivers	Fixture Size
2.2-2.0-4.5	RDUX	2	8'	2	8'	2	6'	0	0	4	6'	5	6'
8.0-2.0	RDUX	8	6'	0	0	2	4'	0	0	0	0	0	0



RDU Configuration & Submittal Form