

REMOTE DRIVER UNIT

Max Rating 1720 W Class 2 Electrical Device
 UL 924, UL 2108, NEMA Rating 1
 Sustainably Constructed
 100% Recycled Aluminum
 Controls Agnostic
 Localized On/Off Switch
 Pre-configured/Pre-wired Zones

Ambient Operating Temperatures: 0°C to 50°C
 Humidity: 5% to 95% RH Non-condensing

277 VAC/1.8 A, 50-60 Hz
 120 VAC/4.2 A, 50-60 Hz

<150' - 18/2 GA Wiring
 >150' - 16/2 GA Wiring



	RDUXX	RDU14	RDU12	RDU6
Weight	42 lbs	30 lbs	25 lbs	14 lbs
W x H x D	28.5" x 27" x 4.5"	21.5" x 27" x 4.5"	19" x 27" x 4.5"	12" x 27" x 4.5"
Drivers	Up to 20	Up to 14	Up to 12	Up to 6

	Single Controls Sidecar	Dual Controls Sidecar
SKU	C	C2
Dimensions w/Localized Switch Box	17.94" X 12.78" X 5.81 +13.50 lbs	26.6" X 12.78" X 5.81 +25.25 lbs
Controllers	1 Dimming 2 Emergency	2 Dimming 4 Emergency
Zones	1-3 Dimming 2 Emergency	2-6 Dimming 4 Emergency

ORDERING INFORMATION

REMOTE DRIVER UNIT

- RDUXX-20 drivers
- RDU14-14 drivers
- RDU12-12 drivers
- RDU6-6 drivers

OPTIONAL CONTROLS SIDECAR*

- C- Single Controls Sidecar
- C2-Dual Controls Sidecar

*CONTROLS NOT INCLUDED

ZONE CONFIGURATION

Examples		ZONE 1				ZONE 2				ZONE 3			
		NORMAL		EMERGENCY		NORMAL		EMERGENCY		NORMAL		EMERGENCY	
Customer PN	Product	Drivers	Fixture Size	Drivers	Fixture Size	Drivers	Fixture Size	Drivers	Fixture Size	Drivers	Fixture Size	Drivers	Fixture Size
2.2-2.0-4.5	RDUXX	2	8'	2	8'	2	6'	0	0	4	6'	5	6'
8.0-2.0	RDUXX	8	6'	0	0	2	4'	0	0	0	0	0	0



RDU Configuration & Submittal Form